



Audio Routing Switcher

Model 1T-SW4x1ARL

tvoneTASK Series Routing Switchers are ultra compact, high performance products designed to meet the most demanding requirements for signal distribution. The 1T-SW4x1ARL is a 4x1 Stereo Audio Routing Switcher with RCA connectors. Audio Bandwidth of 20Hz to 20KHz insures that the stereo audio output is identical to the source signals. Input selection is via front panel Push Buttons or by IR Remote Control. It is 12VDC powered and a small In-Plug Power Adapter is included. For best performance, use high-grade output cables such as our professional Z-Plus type.



1T-SW4x1ARL



Key Features of the Audio Routing Switcher

- Ultra Compact, High Performance Unit
- 20Hz to 20KHz Audio Bandwidth
- 8 Inputs, Right & Left Channel Stereo
- Push Button and IR Inputs Selection
- Rugged Metal Case
- Locking DC Power Connector for Security

Specifications

Audio Routing Switcher

1T-SW4x1ARL 4x1 Stereo Audio (R-L)
Connectors RCA

Audio Performance

Bandwidth 20Hz to 20KHz, +/- 0.1db
Impedance 20KΩ
Distortion <0.5db
Isolation >70db
Signal to Noise Ratio >70db
THD <0.3% (2nd Harmonic)
Signal Gain Unity

Mechanical

Size (H-W-D) 1"x7"x4" (25x175x100mm)
Weight (Net) 1.5 lbs (680g)

Warranty

Limited Warranty 2 Years Parts and Labor

Environmental

Operating Temperature +32° to +120° F (0° to +48° C)
Operating Humidity 10% to 85%, Non-condensing
Storage Temperature -40° to +150° F (-40° to +65° C)
Storage Humidity 10% to 85%, Non-condensing

Power Requirement

External Power Supply 12VDC @ 500mA Maximum

Regulatory Approvals

Amplifier Units FCC, CE
Power Supplies UL, CE, CSA

Accessories Included

1x AC Power Adapter 115VAC to 12VDC @ 500mA
1x IR Remote Control 38KHz Frequency Band

Panel Drawing

